# The assessment of claystone, quartz and coconut shell charcoal for adsorbing heavy metals ions in acid mine drainage

by Faisol Mukarom

**Submission date:** 21-Dec-2022 06:29PM (UTC-0500)

**Submission ID:** 1985671695

File name: Mukarrom\_2020\_IOP\_Conf.\_Ser.\_\_Mater.\_Sci.\_Eng.\_858\_012040.pdf (511.8K)

Word count: 2822 Character count: 14241



### **PAPER · OPEN ACCESS**

The assessment of claystone, quartz and coconut shell charcoal for adsorbing heavy metals ions in acid mine drainage

15 To cite this article: F Mukarrom et al 2020 IOP Conf. Ser.: Mater. Sci. Eng. 858 012040



### You may also like

The Effectiveness of Zeolite/Claystone/Activated Charcoal Composite in Reducing Levels of Mercury (Hg) in the Waste Resulting from the Activities of Unlicensed Gold Mining (PETI) in Sintang

Dwi Rizaldi Hatmoko, Ari Handono Ramelan and Pranoto

Modelling of oedometric compression and swelling behaviour of the Callovo-Oxfordien claystone Song Xiangdong

Assessment of radiological health risk and radiogenic heat production changeability of different sedimentary rocks at Gabal Um Hamd, Southwestern Sinai, Egypt Aya M Zaghloul, Hosnia M Abu-Zeid, Ibrahim E El Aassy et al.



# The assessment of claystone, quartz and coconut shell charcoal for adsorbing heavy metals ions in acid mine drainage

### F Mukarrom<sup>1,2</sup>, Pranoto, R Karsidi, E Gravitiani, F Astuti, W Maharditya

<sup>1</sup>Doctorate Program of Enviromental Science, Postgraduate, Sebelas Maret University <sup>2</sup>Mining Engineering Department, Institut Teknologi Nasional Yogyakarta, Yogyakarta

E-mail:faisolmk@student.uns.ac.id

Abstract. This research aims to determine the assessment of claystone, quartz and coconut shell charcoal for adsorbing heavy metals ions in acid mine drainage. Claystone is activated by using NaOH 3M, quartz sand is activated by using Na2CO3, while coconut shell charcoal is activated with HCl 4M. The adsorbent characterization was done by Fourier Transform Infrared Analyzer (FTIR) and X-Ray Diffraction (XRD). The results of the characterization of claystone FTIR showed the presence of active groups of silanol (Si-OH) and aluminol (Al-OH), XRD claystone characterization showed the presence of montmorillonite, kaolinite, illite and quartz minerals. While the results of FTIR characterization of quartz sand showed the presence of active groups of silanol (Si-OH) and siloxan (Si-O-Si), XRD characterization of quartz sand showed the presence of quartz mineral content. Furthermore, coconut shell charcoal showed the presence of hydroxyl (OH) and carboxyl active groups. (COOH) which is known from FTIR analysis as well as the mineral content of cristobalite, fayalite and manganoan which are known from XRD analysis. From the results of the FTIR and XRD analysis, it can be concluded that the three adsorbents have the potential as adsorbents. So that they can be used as an acid mine water absorber.

### 1. Introduction

Mining industry has several distinctive characteristics. Each phase of the activity requires land clearing (deforestation), land and and minerals excavations in large volumes that can make changes the landscape. Mining activities cause significant changes of the landscape will lead to the degradation of environmental function and quality [1], which include the potential of erosion, sedimentation, decreased air quality, the forming of acid mine drainage, and enlowering land productivity. The elements of how metals in acid mine drainage has serious effects on human health. Toxicologically, this heavy metal can be divided into two types. The first type is an essential heavy metal, where its presence an amount is needed by living organisms, but in such exceed amount in human's body's cause toxic effects. Some of these heavy metals include Zn, Cu, Fe, Co, Mn and so on. The second type is an essential heavy metals in the human's body. These heavy metals are not yet known for its benefits such as Hg, Cd, Pb, Cr and others. Active treatment method of acid mine draiange is able to precipitate dissolved metals and form sludge or mud deposit [2].

One of the passive treatment methods which is considerable is the adsorption method. The availability and the affordability of the adsorbent are very important. The abundant availability and low perational

costs are also as important factors in implementing the method. This research will use claystone, coconut shell charcoal, quartz sand and zeolite as the adsorbtion media. Claystone, could be perform as adsorbent since it is composed from aluminum granules and fine silica. This mineral known has a strong adsorption (sorption) on certain heavy metals dissolved in water [3]. Quartz could be used as an adsorbent because it has a size of sand which is dominated by silica mineral (SiO<sub>2</sub>) hexagonal texture, in its formation crystallized. Utilization of coconut shell one of which is used as charcoal for fuel and can also be used as an adsorbent. Coconut shell is the best material used as activated carbon, because activated carbon produced from coconut shell has carboxyl (COOH) and hydroxyl (OH) functional groups, more micropores, smaller ash content, high solubility in high water and high reactivity [4].

### 2. Experimental

2.1. Materials

16

Claystone, quartz, coconut shell, NaOH p.a (Merck), HCl p.a (Merck), Na<sub>2</sub>CO<sub>3</sub> p.a (Merck).

### 2.2. Preparation of Adsorbent

Claystone is cleaned from impurities and dried b<sub>12</sub> erating it in the open air until it is dry, then claystone is crushed until smooth. Claystone is then sifted with a 150 mesh sieve. Powder that escapes 150 mesh is immersed in distilled water and filtered, then dried at 105 °C for 4 hours. The quartz sand obtained is cleaned of impurities, sifted and finely ground. After smooth, proceed with a sieve size of 100 mesh. Then wash with 0.1 M HNO<sub>3</sub> while stirring with a magnetic stirrer for 1 hour. Washing is done 3 times and the residue obtained is dried [5]. The coconut shell obtained was then cut into small pieces, washed 3 times, dried in the sun to dry, purified 400 °C for 1 hour, grinded and sieved using a 150 mesh size sieve [6]. Adsorbents were characterized using FTIR and XRD.

### 2.3. Adsorbent Activation

The claystoneas much 50 gram is mixed with 250 mL of NaOH 3 M solution. The mixture is stirred at 70 °C for 5 hours then cooled, filtered and washed with distilled water to a neutral pH. Furthermore, activated claystone is dried in an oven at 105 °C for 4 hours [7]. 165 g of quartz sand and 135 g of sodium bicarbonate are mixed and the mixing process is carried out evenly. Then put in a crucial and then heated to a temperature of 1100 °C for 2 hours. Then the melt is cooled and crushed into powder [8]. The coconut shell charcoal as much 50 gr soaked with 100 mL 4 M HCl saution for 24 hours, then filtered and washed with distilled water. The activated carbon produced is then dried in an oven at 110 °C for 3 hours, then cooled in a desiccator [9]. Activated adsorbents were characterized by FTIR and XRD.

### 20

### 3. Result and discussion

### 3.1. FTIR Characterization

### 3.1.1. Claystone

The changes of claystone before and after activation such as shifting of wave numbers from 1031 cm<sup>-1</sup> to 1033 cm<sup>-1</sup> in Si-O-Si / Al-O-Al groups and wave numbers from 912 cm<sup>-1</sup> to 916 cm<sup>-1</sup> in Al groups -OH which shows an increase in intensity because the impurities have been lost during the activation process so that the functional groups become more active. The absorption peak of Al-OH-Al, -OH, H-O-H has decreased intensity.




Figure 1. FTIR of claystone before (a) and after activation (b)

Table 1. Comparison of FTIR claystone adsorption before and after activation

		W	Wavelength (cm <sup>-1</sup> )		
No	Functional Group	Reference	Before activation	After activation	
1	Al-OH-Al	3616[10]	3698; 3623	3698; 3621	
2	-OH	3500-3400[11]	3425	3414	
3	Н-О-Н	1639[12]	1631	1628	
4	Si-O-Si / Al-O-Al	$1039^{[10]}$	1031	1033	
5	Al-OH	920-690[13]	912	916	
6	Si-O / Al-O	470,6[14]	468	468	

### 3.1.2 Quartz sand

There are some differences between quartz sand before and after activation such as the shifting of the wave number from 3432 cm<sup>-1</sup> to 3436 cm<sup>-1</sup> in the -OH strech group and the wave number from 1628 cm<sup>-1</sup> to 1635 cm<sup>-1</sup> in the HOH bend group experiencing increased intensity because impurities have bee clost during the activation process so that functional groups become more active. The peak absorption of Si-O-Si asymmetric stretch, Si-O-Si symmetric stretch and O-Si-O bend have decreased intensity which is possible because the pegotor substance on the surface of quartz sand has dissolved by the activation but not to eliminate the absorption of functional groups.




Figure 2. FTIR spectra of quartz sand before (a) and after activation (b)

Table 2. Comparison of FTIR quartz sand adsorption before and after activation

		Wavelength (cm <sup>-1</sup> )			
No	Functional Group	Reference	Before activation	After activation	
1	O-H stretch	3550-200[15]	3432	3436	
2	H-O-H bend	1641[16]	1628	1635; 1437	
3	Si-O-Si asymmetric strech	$1076^{[17]}$	1084	1022	
4	Si-O-Si symmetric strech	$771^{[17]}$	794	758	
5	O-Si-O bend	461[18]	456	449	

### 3.1.3. Coconut shell charcoal

There are some difference steween coconut shell charcoal before and after activation such as shifting the wave number f 22 3427 cm<sup>-1</sup> to 3421 cm<sup>-1</sup> which shows the absorption of the -OH group experiencing peak widening. The absorption peaks of C = O, C = C, and C-O after activation look sharper indicating an increase in absorption intensity. Increased intensity is possible because the impurities in the coconut shell charcoal have dissolved by the activation.




Figure 3. FTIR spectra of coconut shell charcoal before (a) and after activation (b)

Table 3. Comparison of FTIR coconut shell charcoal adsorption before and after activation

		,	Wavelength (cm <sup>-1</sup> )			
No	Functional Group	Reference	Before activation	After activation		
1	О-Н	3425[19]	3427	3421		
2	C=O	$1705^{[19]}$	1701	1705		
3	C=C	$1589^{[19]}$	1582	1576		
4	C-O	1300-800[15]	873	914; 1037		

### 3.2. XRD Characterization

### 3.2.1. Claystone

The results of XRD clystone analysis before and after activation showed that the presence of minerals such as kaolinite (K), montmorillonite (M), illit (I) and quartz (Q) as evidenced by the appearance of diffraction peaks at  $2\theta$ . Before claystone activation, kaolinite minerals appeared at  $2\theta = 35.02^{\circ}$  and  $32.09^{\circ}$ , montmorillonite minerals appeared at  $2\theta = 5.34^{\circ}$ ;  $19.85^{\circ}$  and  $62.05^{\circ}$ , illit minerals at  $2\theta = 26.70^{\circ}$  and quartz minerals at  $2\theta = 68.29^{\circ}$ . On the active claystone the kaolinite mineral appeared at  $2\theta = 30.20^{\circ}$ ;  $39.65^{\circ}$ ;  $60.11^{\circ}$ , montmorillonite minerals appear at  $2\theta = 5.55^{\circ}$ ;  $20.10^{\circ}$ ; and  $62.05^{\circ}$ , illite mineral at  $2\theta = 26.89^{\circ}$  and quartz mineral at  $2\theta = 68.37^{\circ}$ . The diffractogram comparison before and after activation shows a decrease in intensity and the appearance of new peaks. The decrease in the intensity of each mineral shows that the crystal structure becomes amorphous.




Figure 4. XRD diffractograms of claystone before (a) and after activation (b)  $\,$ 

### 3.2.2. Quartz sand




Figure 5. XRD diffractograms of quartz sand before (a) and after activation (b)  $\,$ 

The results of XRD analysis of quartz sand before and after activation indicate the presence of quartz mineral content (Q) as evidenced by the appearance of diffraction peaks at 2 $\theta$ . Figure 5 shows that the quartz mineral peaks appear at  $2\theta = 20^{\circ}$ ,  $26^{\circ}$ ,  $50^{\circ}$ ,  $54^{\circ}$ , and  $68^{\circ}$ . In active quartz sand quartz minerals appear at  $2\theta = 14^{\circ}$ ,  $16^{\circ}$ ,  $21^{\circ}$ ,  $23^{\circ}$ ,  $27^{\circ}$ ,  $32^{\circ}$  and  $38^{\circ}$ . The diffractogram comparison before and after activation shows a decrease in intensity and the appearance of new peaks. The decrease in the intensity of each mineral shows that the crystal structure becomes amorphous.

### 3.2.3. Coconut shell charcoal

The coconut shell charcoal diffractogram was identified in the cristobalite (C), fayalite (F) and manganoan (M) minerals found in the ICSD (Inorganic Crystal Structure Database). The peak of the coconut shell charcoal diffraction before activation is shown at  $2\theta = 24.22^{\circ}$  which is the mineral cristobalite while the peak of the coconut shell charcoal diffraction after activation is shown at  $2\theta = 21.91^{\circ}$  (cristobalite),  $26.723^{\circ}$  (fayalite),  $27.86^{\circ}$  (manganoan) and  $35.84^{\circ}$  (manganoan + fayalite). The diffractogram comparison after activation shows the appearance of a new peak. The appearance of a new peak indicates that the impurity has dissolved due to the activation process. Dissolution of impurities will open the pores on the surface of the coconut shell charcoal and cause an increase in the mineral content.




Figure 6. XRD diffractograms of coconut shell charcoal before (a) and after activation (b)

### 4. Conclusion

The results of FTIR characterization showed there are active groups in all three materials. The characterization of claystone showed there are active group 24f cyanol (Si-OH) and aluminol (Al-OH), FTIR characterization of quartz sand showed there are active groups of silanol (Si-OH) and siloxane (Si-OSi) and the characterization of coconut shell charcoal showed there are hydroxyl (OH) and carboxyl (COOH) active groups. XRD claystone characterization showed the presence of montmorillonite, kaolinite, illite and quartz minerals. Characterization of quartz sand shows the presence of quartz minerals, and characterization of coconut shell charcoal shows the mineral content of cristobalite, fayalite and manganoan, so it can be concluded that the three materials have the potential as adsorbents that can be used as absorbers of acid mine water.



### Reference

- [1] Ranjan R 2019 JOM FMIPA. 2(1) 63-69.
- [2] Prianto F A 2016 Institut Pertanian Bogor 5.
- [3] Musso T Parolo M, Pettinari G, and Francisca F 2014 Journal of Environmental Management 146 50-58.
- [4] Pambayun G S, Yulianto R Y, Rachimoellah M, and Putri E M 2013 Jurnal Teknik Pomit. 2 116-120.
- [5] Lesbani A 2015 Jurnal Penelitian Sains 14(4) 41-46.
- [6] Rahayu L H, Purnavita S, and Sriyana H 2014 Jurnal Momentum 10(1) 47-53.
- [7] Guo X, Yao Y, Yin G, Kang Y, Luo Y, and Zhuo L 2008 Applied Clay Science 40 20-26.
- [8] Las T, Florentinus F, and Afit H 2011 Valensi 2(2) 368-378.
- [9] Nurhasni, Florentinus F, and Qosim S 2012 Valensi 2(4) 516-525.
- [10] Masindi V, Mugera W G, Harganani T, and Marinda D 2017 Journal of Water Process Engineering 15 2-7.
- [11] Trabelsi W, and Ali T 2017 Journal of African Earth Sciences 129 647-658.
- [12] Sari A, Mustafa T, Demirhan C, and Mustafa S 2007 Journal of Hazardous Materials 149 283-291.
- [13] Mahmoudi S, Bennour A, Meguebli A, Srasra E, and Zargouni F 2016 Applied Clay Science 127-128 78-87
- [14] Wogo HE, Febri ON, and Putra JPT 2013 Jurnal Sains dan Terapan Kimia 7(1) 29-41.
- [15] Silverstain R M, and Webster F X 2000 Spectrometric Identification of Organic Compound, 60th edn. (New York: John Wiley and Sons, Inc).
- [16] Dewanto A S, and Munasir 2016 Jurnal Inovasi Fisika Indonesia (IFI) 5(2) 1-4.
- [17] Du G H, Liu Z I, Xia X, Chu Q, and Zhang S M 2006 J Sol-Gel Sci Techn 39 285-291.
- [18] Ahangaran F, Ali H, and Sirous N 2013 International Nano Letters 3(23) 1-5.
- [19] Kurniati F D, Pardoyo, and Suhartana 2011 Jurnal Kimia Sains dan Aplikasi 14(3) 72-76.

The assessment of claystone, quartz and coconut shell charcoal for adsorbing heavy metals ions in acid mine drainage

	ALITY REPORT				
2 SIMILA	2% ARITY INDEX	20% INTERNET SOURCES	14% PUBLICATIONS	9% STUDENT PA	PERS
PRIMAR	Y SOURCES				
1	eprints.u	ıthm.edu.my			5%
2	WWW.pro	ceedings.com			3%
3	Qiuxiang "Radiation and stor	Zhang, Fang Zh g Liu, Jun Jiang, z on evaluation of ne materials fro ou", Journal of P 022	Zhangsen Che f household ap m residences	n. opliances in	2%
4	COre.ac.l				1 %
5	Sciencero				1%
6	Submitte Student Paper	ed to Universiti	Teknologi Ma	laysia	1 %

link.springer.com

7	Internet Source	1 %
8	www.scirp.org Internet Source	1%
9	ir.nctu.edu.tw Internet Source	1%
10	edocs.tib.eu Internet Source	1%
11	dr.ntu.edu.sg Internet Source	1%
12	smujo.id Internet Source	1%
13	Nia Sasria, Aprina Dewi Rizki, Gusti Umindya Nur Tajalla. "Removal of Lead Ions (Pb <sup>2+</sup> ) Using Acid-Activated Clay from East Kalimantan", Materials Science Forum, 2022	1%
14	W Dahani, I Marwanza, R Safitri, A B Pambudi, M I Rizki. "The Relevancy of Mineral Composition to Rock Shear Strength in Kaliwadas Hills, Karangsambung, Kebumen", IOP Conference Series: Materials Science and Engineering, 2019 Publication	1%
15	ojs.stmikpringsewu.ac.id	1 %

16	Peter Grauel, Hamilton Varela, Katharina Krischer. "Spatial bifurcations of fixed points and limit cycles during the electrochemical oxidation of H2 on Pt ring-electrodes", Faraday Discussions, 2002 Publication	<1%
17	Submitted to Universitas Muhammadiyah Surakarta Student Paper	<1%
18	download.garuda.kemdikbud.go.id Internet Source	<1%
19	patents.justia.com Internet Source	<1%
20	Industrial Lubrication and Tribology, Volume 66, Issue 1 (2014-03-28) Publication	<1%
21	Sadek, O.M "Na-montmorillonite clay as thermal energy storage material", Thermochimica Acta, 20010404	<1 %
22	coek.info Internet Source	<1%
23	www.coursehero.com Internet Source	<1%
24	ojs3.unpatti.ac.id Internet Source	<1%

26

Seri MAULINA, Gewa HANDIKA, Irvan, Apri Heri ISWANTO. "Quality Comparison of Activated Carbon Produced From Oil Palm Fronds by Chemical Activation Using Sodium Carbonate versus Sodium Chloride", Journal of the Korean Wood Science and Technology, 2020

<1%

Publication

Exclude quotes

On

Exclude bibliography

Exclude matches

Off

## The assessment of claystone, quartz and coconut shell charcoal for adsorbing heavy metals ions in acid mine drainage

GRADEMARK REPORT	
FINAL GRADE	GENERAL COMMENTS
/0	Instructor
PAGE 1	
PAGE 2	
PAGE 3	
PAGE 4	
PAGE 5	
PAGE 6	
PAGE 7	
PAGE 8	
PAGE 9	